1. MAGNET :

Two bodies even after being neutral (showing no electric interaction) may attract / repel strongly if they have a special property. This property is known as magnetism. The force with which they attract or repel is called magnetic force. Those bodies are called magnets. Later on we will see that it is due to circulating currents inside the atoms. Magnets are found in different shape but for many experimental purposes, a bar magnet is frequently used. When a bar magnet is suspended at its middle, as shown, and it is free to rotate in the horizontal plane it always comes to equilibrium in a fixed direction.

One end of the magnet (say A) is directed approximately towards north and the other end (say B) approximately towards south. This observation is made everywhere on the earth. Due to this reason the end A, which points towards north direction is called NORTH POLE and the other end which points towards south direction is called SOUTH POLE. They can be marked as 'N' and 'S' on the magnet. This property can be used to determine the north or south direction anywhere on the earth and indirectly east



and west also if they are not known by other method (like rising of sun and setting of the sun). This method is used by navigators of ships and aeroplanes. The directions are as shown in the figure. All directions E, W, N, S are in the horizontal plane.

The magnet rotates due to the earths magnetic field about which we will discuss later in this chapter.

1.1 Pole strength magnetic dipole and magnetic dipole moment :

(i)

A magnet always has two poles 'N' and 'S' and like poles of two magnets repel each other and the unlike poles of two magnets attract each other they form action reaction pair.

S



The poles of the same magnet do not come to meet each other due to attraction. They are maintained we cannot get two isolated poles by cutting the magnet from the middle. The other end becomes pole of opposite nature. So, 'N' and 'S' always exist together.

(ii)



They are known as +ve and –ve poles. North pole is treated as positive pole (or positive magnetic charge) and the south pole is treated as –ve pole (or –ve magnetic charge). They are quantitatively represented by their "POLE STRENGTH" +m and –m respectively (just like we have charges +q and –q

in electrostatics). Pole strength is a scalar quantity and represents the strength of the pole hence, of the magnet also).

A magnet can be treated as a dipole since it always has two opposite poles (just like in electric dipole we have two opposite charges -q and +q). It is called MAGNETIC DIPOLE and it has a MAGNETIC DIPOLE MOMENT. It is represented by \vec{M} . It is a vector quantity. It's direction is from -m to +m that means from 'S' to 'N')



 $M = m.\ell_m$ here $\ell_m =$ magnetic length of the magnet. ℓ_m is slightly less than ℓ_g (it is geometrical length of the magnet = end to end distance). The 'N' and 'S' are not located exactly at the ends of the magnet. For calculation purposes we can assume $\ell_m = \ell_g$ [Actually $\ell_m/\ell_g \simeq 0.84$].

The units of m and M will be mentioned afterwards where you can remember and understand.

1.2 Magnetic field and strength of magnetic field.

The physical space around a magnetic pole has special influence due to which other pole experience a force. That special influence is called MAGNETIC FIELD and that force is called 'MAGNETIC FORCE'. This field is qualitatively represented by 'STRENGTH OF MAGNETIC FIELD' or "MAGNETIC INDUCTION" as "MACNETIC FIELD FORCE".

INDUCTION" or "MAGNETIC FLUX DENSITY". It is represented by \vec{B} . It is a vector quantity.

Definition of B: The magnetic force experienced by a north pole of unit pole strength at a point due to some other poles (called source) is called the strength of magnetic field at that point due to the source.

Mathematically, $\vec{B} = \frac{F}{m}$

Here \vec{F} = magnetic force on pole of pole strength m. m may be +ve or –ve and of any value.

S.I. unit of \vec{B} is **Tesla** or **Weber/m²** (abbreviated as T and Wb/m²).

We can also write $\vec{F} = m\vec{B}$. According to this direction of on +ve pole (North pole) will be in the direction of field and on –ve pole (south pole) it will be opposite to the direction of \vec{B} .

The field generated by sources does not depend on the test pole (for its any value and any sign).

(a) B due to various source

(i) Due to a single pole : (Similar to the case of a point charge in electrostatics)



IIT-JEE

Direction of B due to north pole and due to south poles are as shown in vector form $\vec{B} = \left(\frac{\mu_0}{4\pi}\right) \frac{m}{r^3} \vec{r}$ here m is with sign and \vec{r} = position vector of the test point with respect to the pole.

(ii) Due to a bar magnet : (Same as the case of electric dipole in electrostatics) Independent case never found. Always 'N' and 'S' exist together as magnet.



1.3

3 Magnetic lines of force of a bar magnet :



Example 1. Find the magnetic force on a short magnet of magnetic dipole moment M₂ due to another short magnet of magnetic dipole moment M₁.



Solution : To find the magnetic force we will use the formula of 'B' due to a magnet. We will also assume m and –m as pole strengths of 'N' and 'S' of M₂. Also length of M₂ as 2a. B₁ and B₂ are the strengths of the magnetic field due to M₁ at +m and –m respectively. They experience magnetic forces F₁ and F₂ as shown.

$$\therefore \quad \mathsf{F}_{\mathsf{res}} = \mathsf{F}_1 - \mathsf{F}_2 = 2\left(\frac{\mu_0}{4\pi}\right)\mathsf{M}_1\mathsf{m}\left[\left(\frac{1}{(\mathsf{r}-\mathsf{a})^3}\right) - \left(\frac{1}{(\mathsf{r}+\mathsf{a})^3}\right)\right]$$
$$= 2 \quad \left(\frac{\mu_0}{4\pi}\right)\frac{\mathsf{M}_1\mathsf{m}}{\mathsf{r}^3}\left[\left(1 - \frac{\mathsf{a}}{\mathsf{r}}\right)^{-3} - \left(1 + \frac{\mathsf{a}}{\mathsf{r}}\right)^{-3}\right]$$

By using acceleration, Binomial expansion, and neglecting terms of high power we get

$$F_{\text{res}} = 2\left(\frac{\mu_0}{4\pi}\right) \frac{M_1 m}{r^3} \left[1 + \frac{3a}{r} - 1 + \frac{3a}{r}\right]$$
$$= 2\left(\frac{\mu_0}{4\pi}\right) \frac{M_1 m}{r^3} \frac{6a}{r} = 2\left(\frac{\mu_0}{4\pi}\right) \frac{M_1 3M_2}{r^4} = 6\left(\frac{\mu_0}{4\pi}\right) \frac{M_1 M_2}{r^4}$$

Direction of Fres is towards right.

Alternative Method :

$$B = \frac{\mu_0}{4\pi} \cdot \frac{2M_1}{r^3} \qquad \Rightarrow \qquad \frac{dB}{dr} = -\frac{\mu_0}{4\pi} \times \frac{6M_1}{r^4}$$
$$F = -M_2 \times \frac{dB}{dr} \qquad \Rightarrow \qquad F = \left(\frac{\mu_0}{4\pi}\right) \frac{6M_1M_2}{r^4}$$

Example 2. A magnet is 10 cm long and its pole strength is 120 CGS units (1 CGS unit of pole strength = 0.1 A-m). Find the magnitude of the magnetic field B at a point on its axis at a distance 20 cm from it.

Solution : The pole strength is m = 120 CGS units = 12A-m.

Magnetic length is $2\ell = 10$ cm or $\ell = 0.05$ m.

Distance from the magnet is d = 20 cm = 0.2 m. The field B at a point in end-on position is

$$B = \frac{\mu_0}{4\pi} \frac{2Md}{(d^2 - \ell^2)^2} = \frac{\mu_0}{4\pi} \frac{4m\ell d}{(d^2 - \ell^2)^2}$$
$$= \left(10^{-7} \frac{T - m}{A}\right) \frac{4 \times (12A - m) \times (0.05m) \times (0.2m)}{[(0.2m)^2 - (0.05m)^2]^2}$$
$$= 3.4 \times 10^{-5} \text{ T}.$$

Example 3. Find the magnetic field due to a dipole of magnetic moment 1.2 A-m² at a point 1 m away from it in a direction making an angle of 60° with the dipole-axis.

Solution : The magnitude of the field is $B = \frac{\mu_0}{4\pi} \frac{M}{r^3} \sqrt{1 + 3\cos^2 \theta}$

$$= \left(10^{-7} \frac{T-m}{A}\right) \frac{1.2A - m^2}{1m^3} \quad \sqrt{1 + 3\cos^2 60^0} = 1.6 \times 10^{-7} \text{ T}.$$

The direction of the field makes an angle $\boldsymbol{\alpha}$ with the radial line where

$$\tan \alpha = \frac{\tan \theta}{2} = \frac{\sqrt{3}}{2}$$

Example 4. Figure shows two identical magnetic dipoles a and b of magnetic moments M each, placed at a separation d, with their axes perpendicular to each other. Find the magnetic field at the point P midway between the dipoles.



Solution :

n: The point P is in end-on position for the dipole (a) and in broadside-on position for the dipole (b). The magnetic field at P due to a is $B_a = \frac{\mu_0}{4\pi} \frac{2M}{(d/2)^3}$ along the axis of a, and that due to b is

 $B_{b} = \frac{\mu_{0}}{4\pi} \frac{M}{(d/2)^{3}}$ parallel to the axis of b as shown in figure. The resultant field at P is, therefore.

$$= \frac{\mu_0 M}{4\pi (d/2)^3} \sqrt{1^2 + 2^2} = \frac{2\sqrt{5}\mu_0 M}{\pi d^3}$$

The direction of this field makes an angle α with B_a such that tan α = B_b/B_a = 1/2.

1.4 Magnet in an external uniform magnetic field :

(same as case of electric dipole) $F_{res} = 0$ (for any angle)

 $B = \overline{B^2 \perp B^2}$

 $\tau = MB \sin \theta$

* here θ is angle between \vec{B} and \vec{M}

Note :

• $\vec{\tau}$ acts such that it tries to make $\vec{M} \times \vec{B}$.

•
$$\tilde{\tau}$$
 is same about every point of the dipole it's potential energy is

 $U = -MB\cos\theta = -\vec{M}\cdot\vec{B}$

 $\theta = 0^{\circ}$ is stable equilibrium

 $\theta = \pi$ is unstable equilibrium

for small ' θ ' the dipole performs SHM about θ = 0° position

 τ = – MB sin θ ;

I α = – MB sin θ

for small θ , sin $\theta \simeq \theta$

$$\alpha = -\left(\frac{\mathsf{MB}}{\mathsf{I}}\right)\theta$$

Angular frequency of SHM

$$\omega = \sqrt{\frac{\mathsf{MB}}{\mathsf{I}}} = \frac{2\pi}{\mathsf{T}} \qquad \Rightarrow \qquad \mathsf{T} = 2\pi \sqrt{\frac{\mathsf{I}}{\mathsf{MB}}}$$

here $I = I_{cm}$ if the dipole is free to rotate = I_{hinge} if the dipole is hinged

A bar magnet having a magnetic moment of 1.0×10^{-4} J/T is free to rotate in a horizontal plane. A horizontal magnetic field B = 4×10^{-5} T exists in the space. Find the work done in rotating the magnet slowly from a direction parallel to the field to a direction 60° from the field.

Solution :

Example 5.

 $= (-MB \cos\theta_2) - (-MB \cos\theta_1) = -MB (\cos 60^\circ - \cos 0^\circ)$

The work done by the external agent = change in potential energy

$$= \frac{1}{2} \text{MB} = \frac{1}{2} \times (1.0 \times 10^4 \text{ J/T}) (4 \times 10^{-5} \text{ T}) = 0.2 \text{ J}$$





Example 6. Solution :	A magnet of magnetic dipole moment M is released in a uniform magnetic field of induction B from the position shown in the figure. Find : (i) Its kinetic energy at $\theta = 90^{\circ}$ (ii) its maximum kinetic energy during the motion. (iii) will it perform SHM? oscillation ? Periodic motion? What is its amplitude? (i) Apply energy conservation at $\theta = 120^{\circ}$ and $\theta = 90^{\circ}$
	$-$ MB cos 120° + 0 = $-$ MB cos 90° + (K.E.) \Rightarrow KE = $\frac{\text{MB}}{2}$ Ans.
	(ii) K.E. will be maximum where P.E. is minimum. P.E. is minimum at $\theta = 0^{\circ}$. Now apply energy conservation between $\theta = 120^{\circ}$ and $\theta = 0^{\circ}$. $- \text{ mB cos } 120^{\circ} + 0 = -\text{mB cos } 0^{\circ} + (\text{KE})_{\text{max}}$
	$\frac{3}{2}$ (KE) _{max} = MB Ans.
	The K.E. is max at $\theta = 0^{\circ}$ can also be proved by torque method. From $\theta = 120^{\circ}$ to $\theta = 0^{\circ}$ the torque always acts on the dipole in the same direction (here it is clockwise) so its K.E. keeps on increases till $\theta = 0^{\circ}$. Beyond that τ reverses its direction and then K.E. starts decreasing \therefore $\theta = 0^{\circ}$ is the orientation of M to here the maximum K.E. (iii) Since ' θ ' is not small. \therefore the motion is not S.H.M. but it is oscillatory and periodic amplitude is 120°.
Example 7.	A bar magnet of mass 100 g, length 7.0 cm, width 1.0 cm and height 0.50 cm takes $\pi/2$ seconds
	25μT.
	(a) Find the magnetic moment of the magnet.(b) If the magnet is put in the magnetometer with its 0.50 cm edge horizontal, what would be the time period?
Solution :	(a) The moment of inertia of the magnet about the axis of rotation is $I = \frac{m'}{12} (L^2 + b^2)$
	$\frac{100 \times 10^{-3}}{12} = [(7 \times 10^{-2})^2 + (1 \times 10^{-2})^2] \text{ kg-m}^2. = \frac{25}{6} \times 10^{-5} \text{ kg-m}^2.$
	We have, $T = 2\pi \sqrt{\frac{I}{MB}}$ or $M = \frac{4\pi^2 I}{BT^2} = \frac{4\pi^2 \times 25 \times 10^{-5} \text{kg/m}^2}{6 \times (25 \times 10^{-6} \text{T}) \times \frac{\pi^2}{4} \text{s}^2} = 27 \text{ A-m}^2.$
	(b) In this case the moment of inertia becomes I' = $\frac{m'}{12}$ (L ² + b ²) where b' = 0.5 cm.
	The time period would be $T' = \sqrt{\frac{I'}{MB}}$ (ii)
	Dividing by equation (i),
	$\frac{T'}{T} = \sqrt{\frac{I'}{I}} = \frac{\sqrt{\frac{11}{12}(L^2 + b^{12})}}{\sqrt{\frac{m'}{12}(L^2 + b^2)}} = \frac{\sqrt{(7cm)^2 + (0.5cm)^2}}{\sqrt{(7cm)^2 + (1.0cm)^2}} = 0.992$
	or $T' = \frac{0.992 \times \pi}{2} s = 0.496\pi s.$

1.5 Magnet in an External Non-uniform Magnetic Field :

No special formulae are applied is such problems. Instead see the force on individual poles and calculate the resistant force torque on the dipole.

Example 8. Find the torque on M_1 due to M_2 .



$$= \left[\left(\frac{\mu_0}{4\pi} \right) \frac{M_2}{(r-a)} m + \frac{\mu_0}{4\pi} \frac{M_2}{(r+a)} m \right] a$$
$$\cong \frac{\mu_0}{4\pi} M_2 m \left(\frac{1}{r^3} + \frac{1}{r^3} \right) a \qquad \because a \ll r$$

$$= \frac{\mu_0 M_2 m}{4\pi} \frac{2}{r^3} a = \frac{\mu_0 M_1 M_2}{4\pi r^3} Ans.$$



2. MAGNETIC EFFECTS OF CURRENT (AND MOVING CHARGE)

It was observed by **OERSTED** that a current carrying wire produces magnetic field nearly it. It can be tested by placing a magnet in the near by space, it will show some movement (deflection or rotation of displacement). This observation shows that current or moving charge produces magnetic field.

2.1 Frame Dependence of **B**.

(a) The motion of anything is a relative term. A charge may appear at rest by an observer (say O₁) and moving at same velocity \vec{v}_1 with respect to observer O₂ and at velocity \vec{v}_2 with respect to observers O₃ then \vec{B} due to that charge w.r.t. O₁ will be zero and w.r. to O₂ and O₃ it will be \vec{B}_1 and



 \vec{B}_2 (that means different)

(b) In a current carrying wire electron move in the opposite direction to that of the current and +ve ions (of the metal) are static w.r.t. the wire. Now if some observer (O₁) moves with velocity V_d in the direction of motion of the electrons then electrons will have zero velocity and +ve ions will have velocity V_d in the downward direction w.r.t. O₁. The density (n) of +ve ions is same as the density of free electrons and their charges are of the same magnitudes

So, w.r.t. O₁ electrons will produce zero magnetic field but +ve ions will produce +ve same \vec{B} due to the current carrying wire does not depend on the reference frame (this is true for any velocity of the observer).

(c) B due to magnet :

B produced by the magnet does not contain the term of velocity

So, we can say that the \vec{B} due magnet does not depend on frame.

2.2 due to a point charge :

A charge particle 'q' has velocity v as shown in the figure. It is at position 'A' at some time. \vec{r} is the position vector of point 'P' w.r. to position of the charge. Then \vec{B} at P due to q is

$$\begin{split} \mathsf{B} = & \left(\frac{\mu_0}{4\pi}\right) \frac{q \mathsf{v} \sin \theta}{r^2} \text{ ; here } \theta = \text{angle between } \vec{\mathsf{v}} \text{ and } \vec{\mathsf{r}} \\ \vec{\mathsf{B}} = & \left(\frac{\mu_0}{4\pi}\right) \frac{q \vec{\mathsf{v}} \times \vec{\mathsf{r}}}{r^3} \text{ ; with sign } \Rightarrow \qquad \vec{\mathsf{B}} \perp \vec{\mathsf{v}} \text{ and also } \vec{\mathsf{B}} \perp \vec{\mathsf{r}} \text{ .} \end{split}$$

Direction of \vec{B} will be found by using the rules of vector product.

2.3 Biot-savart's law (B due to a wire)

It is an experimental law. A current 'i' flows in a wire (may be straight or curved). Due to 'd ℓ ' length of the wire the magnetic field at 'P' is

 $dB \propto i d\ell$

$$\propto \frac{1}{r^2} \Rightarrow \propto \sin \theta$$

$$\Rightarrow dB \propto \frac{id\ell \sin\theta}{r^2} \qquad \Rightarrow \qquad dB = \left(\frac{\mu_0}{4\pi}\right) \frac{id\ell \sin\theta}{r^2} \qquad \Rightarrow \quad \overline{dB} = \left(\frac{\mu_0}{4\pi}\right) \frac{id\ell \times \vec{r}}{r^3}$$

here \vec{r} = position vector of the test point w.r.t. $\vec{d\ell}$

 θ = angle between $\vec{d\ell}$ and \vec{r} . The resultant $\vec{B} = \int \vec{dB}$

Using this fundamental formula we can derive the expression of \vec{B} due to a long wire.

2.3.1 B due to a straight wire :

Due to a straight wire 'PQ' carrying a current 'i' the \vec{B} at A is given by the formula



$$\mathsf{B} = \frac{\mu_0 \mathrm{I}}{4\pi \mathrm{r}} (\sin \theta_1 + \sin \theta_2)$$





(Derivation can be seen in a standard text book like your school book or concept of physics of HCV part-II) Direction :

Due to every element of 'PQ' \vec{B} at A is directed in wards. So its resultant is also directed inwards. It is represented by (x)

The direction of \vec{B} at various points is shown in the figure shown

At points 'C' and 'D' $\vec{B} = 0$ (think how). For the case shown in figure

B at A = $\frac{\mu_0 i}{4\pi r}$ (sin $\theta_2 - \sin\theta_1$) (x)

Shortcut for Direction :

The direction of the magnetic field at a point P due to a straight wire can be found by a slight variation in the right-hand thumb rule. If we stretch the thumb of the right hand along the current and curl our fingers to pass through the point P, the direction of the fingers at P gives the direction of the magnetic field there.

We can draw magnetic field lines on the pattern of electric field lines. A tangent to a magnetic field line given the direction of the magnetic field existing at that point. For a straight wire, the field lines are concentric circles with their centers on the wire and in the plane perpendicular to the wire. There will be infinite number of such lines in the planes parallel to the above mentioned plane.



Example 9. Find resultant magnetic field at 'C' in the figure shown.





Solution : It is clear that 'B' at 'C' due all the wires is directed **O**. Also B at 'C' due PQ and SR is same. Also due to QR and PS is same

$$\therefore B_{\text{res}} = 2(B_{PQ} + B_{SP})$$

$$B_{PQ} = \frac{\mu_0 i}{4\pi \frac{a}{2}} \text{ (sin 60° + sin 60°),}$$

$$B_{sp} = \frac{\mu_0 i}{4\pi \frac{\sqrt{3}a}{2}} \text{ (sin 30° + sin 30°)}$$

$$\Rightarrow B_{\text{res}} = 2\left(\frac{\sqrt{3} \mu_0 i}{2\pi a} + \frac{\mu_0 i}{2\pi a\sqrt{3}}\right) = \frac{4\mu_0 i}{\sqrt{3}\pi a}$$

Example 10. Figure shows a square loop made from a uniform wire. Find the magnetic field at the centre of the square if a battery is connected between the points B and D as shown in the figure



Solution : The current will be equally divided at D. The fields at the centre due to the currents in the wires DA and DC will be equal in magnitude and opposite in direction. The resultant of these two fields will be zero. Similarly, the resultant of the fields due to the wires AB and CB will be zero. Hence, the net field at the centre will be zero.

Special case :

(i) If the wire is infinitely long then the magnetic field at 'P' (as shown in the figure) is given by (using $\theta_1 = \theta_2 = 90^\circ$ and the formula of 'B' due to straight wire)



$$\mathsf{B} = \frac{\mu_0 I}{2\pi r} \Longrightarrow \ \mathsf{B} \propto \frac{I}{r}$$

The direction of \vec{B} at various is as shown in the figure. The magnetic lines of force will be concentric circles around the wire (as shown earlier)

(ii) If the wire is infinitely long but 'P' is as shown in the figure. The direction of \vec{B} at various points is as shown in the figure. At 'P'



$$\mathsf{B} = \frac{\mu_0 I}{4\pi \mathsf{r}}$$

Example 11. In the figure shown there are two parallel long wires (placed in the plane of paper) are carrying currents 2I and I consider points A, C, D on the line perpendicular to both the wires and also in the plane of the paper. The distances are mentioned. Find

(i) B at A, C, D

(ii) position of point on line A C D where \vec{B} is O

Solution : (i) Let us call \vec{B} due to (1) and (2) as \vec{B}_1 and \vec{B}_2 respectively. Then

at A :
$$\vec{B}_1$$
 is \odot and \vec{B}_2 is \bigotimes
B₁ = $\frac{\mu_0 2I}{2\pi a}$ and B₂ = $\frac{\mu_0 I}{2\pi 2a}$
 \therefore B_{res} = B₁- B₂ = $\frac{3}{4} \frac{\mu_0 I}{\pi a} \odot$ Ans.

at C : \vec{B}_1 is \bigotimes and \vec{B}_2 also \bigotimes

$$\therefore \quad \mathsf{B}_{\mathsf{res}} = \mathsf{B}_1 + \mathsf{B}_2 = \frac{\mu_0 2\mathsf{I}}{2\pi \frac{\mathsf{a}}{2}} + \frac{\mu_0 \mathsf{I}}{2\pi \frac{\mathsf{a}}{2}} = \frac{6\mu_0 \mathsf{I}}{2\pi \mathsf{a}} = \frac{3\mu_0 \mathsf{I}}{\pi \mathsf{a}} \bigotimes \quad \mathsf{Ans}.$$

at D : \vec{B}_1 is \bigotimes and \vec{B}_2 is \odot and both are equal in magnitude.

$$\therefore B_{\text{res}} = 0 \qquad \text{Ans.}$$

(ii) It is clear from the above solution that B = 0 at point 'D'.

Example 12. In the figure shown two long wires W_1 and W_2 each carrying current I are placed parallel to each other and parallel to z-axis. The direction of current in W_1 is outward and in W_2 it is inwards. Find the \vec{B} at 'P' and 'Q'.







60° 60° B₂





Example 13.

3. In the figure shown a large metal sheet of width 'w' carries a current I (uniformly distributed in its width 'w'. Find the magnetic field at point 'P' which lies in the plane of the sheet.



Solution : To find 'B' at 'P' the sheet can be considered as collection of large number of infinitely long wires. Take a long wire distance 'x' from 'P' and of width 'dx'. Due to this the magnetic field at 'P' is 'dB'

$$d\mathsf{B} = \frac{\mu_0 \left(\frac{\mathsf{I}}{\mathsf{w}} \mathsf{d} \mathsf{x}\right)}{2\pi \mathsf{x}} \otimes$$

due to each such wire \vec{B} will be directed inwards



2.3.2 B due to circular loop

(a) At centre : Due to each $\vec{d\ell}$ element of the loop \vec{B} at 'c' is inwards (in this case).

$$\mathsf{B} = \frac{\mu_0 \mathsf{N} \mathsf{I}}{2\mathsf{R}}$$

N = No. of turns in the loop.

=
$$\frac{\ell}{2\pi R}$$
; ℓ = length of the loop.

C R

N can be fraction $\left(\frac{1}{4}, \frac{1}{3}, \frac{11}{3}$ etc. $\right)$ or integer

Direction of \vec{B} : The direction of the magnetic field at the centre of a circular wire can be obtained using the right-hand thumb rule. If the fingers are curled along the current, the stretched thumb will point towards the magnetic field (figure).

Another way to find the direction is to look into the loop along its axis. If the current is in anticlockwise direction, the magnetic field is towards the viewer. If the current is in clockwise direction, the field is away from the viewer.



 $N=\frac{1}{2}$

(b) On the axis of the loop : $B = \frac{\mu_0 I}{4R}$ $\frac{\mu_0 NIR^2}{2(R^2 + x^2)^{3/2}}$

N = No. of turns (integer)



Direction can be obtained by right hand thumb rule. curl your fingers in the direction of the current then the direction of the thumb points in the direction of at the points on the axis.

8R

The magnetic field at a point not on the axis is mathematically difficult to calculate. We show qualitatively in figure the magnetic field lines due to a circular current which will give some idea of the field.



2.3.3 A loop as a magnet :

The pattern of the magnetic field is comparable with the magnetic field produced by a bar magnet.



The side 'I' (the side from which the \vec{B} emerges out) of the loop acts as 'NORTH POLE' and side II (the side in which the \vec{B} enters) acts as the 'SOUTH POLE'. It can be verified by studying force on one loop due to a magnet or a loop.



Mathematically

$$B_{axis} = \frac{\mu_0 NIR^2}{2(R^2 + x^2)^{3/2}} \cong \frac{\mu_0 NIR^2}{2x^3} \text{ for } x >> R$$
$$= 2\left(\frac{\mu_0}{4\pi}\right) \left(\frac{IN\pi R^2}{x^3}\right)$$

it is similar to B_{axis} due to magnet = $2\left(\frac{\mu_0}{4\pi}\right)\frac{m}{x^3}$

Magnetic dipole moment of the loop $M = IN\pi R^2$

M = INA for any other shaped loop. Unit of M is Amp. m².

Unit of m (pole strength) = Amp. m

$$\vec{\mathsf{M}} = \mathsf{IN}\vec{\mathsf{A}}$$
 ,

A = unit normal vector for the loop.

To be determined by right hand rule which is also used to determine direction of \vec{B} on the axis. It is also from 'S' side to 'N' side of the loop.

{:: in magnet $M = m\ell$ }



2.3.4 Solenoid :

(i) Solenoid contains large number of circular loops wrapped around a non-conducting cylinder. (it may be a hollow cylinder or it may be a solid cylinder)



(ii) The winding of the wire is uniform direction of the magnetic field is same at all points of the axis.

β)

(iii) \vec{B} on axis (turns should be very close to each others).

$$\mathsf{B} = \frac{\mu_0 \mathsf{n}\mathsf{I}}{2} \; (\cos \,\theta_1 - \cos \,\theta_2)$$

where n : number of turns per unit length.

$$\cos \theta_{1} = \frac{\ell_{1}}{\sqrt{\ell_{1}^{2} + R^{2}}} ; \cos \beta = \frac{\ell_{2}}{\sqrt{\ell_{2}^{2} + R^{2}}} = -\cos \theta_{2}$$
$$B = \frac{\mu_{0} ni}{2} \left[\frac{\ell_{1}}{\sqrt{\ell_{1}^{2} + R^{2}}} + \frac{\ell_{2}}{\sqrt{\ell_{2}^{2} + R^{2}}} \right] = \frac{\mu_{0} ni}{2} (\cos \theta_{1} + \cos \theta_{2})$$



Note :

• Use right hand rule for direction (same as the direction due to loop).

Derivation:

Take an element of width dx at a distance x from point P. [point P is the point on axis at which we are going to calculate magnetic field. Total number of turns in the element dn = ndx where n : number of turns per unit length.

dB =
$$\frac{\mu_0 i R^2}{2(R^2 + x^2)^{3/2}}$$
 (ndx)



$$\mathsf{B} = \int \mathsf{d}\mathsf{B} = \int_{-\ell_1}^{\ell_2} \frac{\mu_0 i \ \mathsf{R}^2 \ \mathsf{n}\mathsf{d}x}{2(\mathsf{R}^2 + \mathsf{x}^2)^{3/2}} = \frac{\mu_0 n i}{2} \left[\frac{\ell_1}{\sqrt{\ell_1^2 + \mathsf{R}^2}} + \frac{\ell_2}{\sqrt{\ell_2^2 + \mathsf{R}^2}} \right] = \frac{\mu_0 n i}{2} \left[\cos\theta_1 - \cos\theta_2 \right]$$

(iv) For 'Ideal Solenoid' :

*Inside (at the mid point)

 $\ell >> R$ or length is infinite

$$\begin{aligned} \theta_1 &\rightarrow 0 \ ; \ \theta_2 &\rightarrow \pi \\ B &= \frac{\mu_0 n i}{2} \ \left[1 - (-1) \right] \end{aligned}$$

B = μ₀ni

If material of the solid cylinder has relative permeability ' μ_r ' then B = $\mu_0\mu_r$ ni

At the ends B = $\frac{\mu_0 ni}{2}$

(v) Comparison between ideal and real solenoid :





Real Solenoid



Example 14. A solenoid of length 0.4 m and diameter 0.6 m consists of a single layer of 1000 turns of fine wire carrying a current of 5.0 x 10⁻³ ampere. Find the magnetic field on the axis at the middle and at the ends of the solenoid. (Given $\mu_0 = 4\pi \times 10^{-7} \frac{V-s}{A-m}$). Solution : $B = \frac{1}{2} \mu_0 ni [\cos \theta_1 - \cos \theta_2] \implies n = \frac{1000}{0.4} = 2500 \text{ per meter}$ $i = 5 \times 10^{-3} \text{ A.}$ (i) $\cos \theta_1 = \frac{0.2}{\sqrt{(0.3)^2 + (0.2)^2}} = \frac{0.2}{\sqrt{0.13}}$ $\cos \theta_2 = \frac{-0.2}{\sqrt{0.13}} \implies B = \frac{1}{2} \times (4 \times \pi \times 10^{-7}) \times 2500 \times 5 \times 10^{-3} \frac{2 \times 0.2}{\sqrt{0.13}} = \frac{\pi \times 10^{-5}}{\sqrt{13}} \text{ T}$ (ii) At the end $\cos \theta_1 = \frac{0.4}{\sqrt{(0.3)^2 + (0.4)^2}} = 0.8$ $\Rightarrow \cos \theta_2 = \cos 90^\circ = 0$ $B = \frac{1}{2} \times (4 \times \pi \times 10^{-7}) \times 2500 \times 5 \times 10^{-3} \frac{2 \times 0.2}{\sqrt{0.13}} = \frac{\pi \times 10^{-5}}{\sqrt{13}} \text{ T}$ $\Rightarrow \cos \theta_2 = \cos 90^\circ = 0$ $B = \frac{1}{2} \times (4 \times \pi \times 10^{-7}) \times 2500 \times 5 \times 10^{-3} \text{ meter}$

2.4 AMPERE's circuital law :

The line integral $\oint \vec{B} \cdot \vec{d\ell}$ on a closed curve of any shape is equal to μ_0 (permeability of free space) times the net current I through the area bounded by the curve.

 $\oint \vec{B} \cdot \vec{d\ell} = \mu_0 I$

Note :

- Line integral is independent of the shape of path and position of wire with in it.
- The statement $\oint \vec{B} \cdot \vec{d\ell} = 0$ does not necessarily mean that $\vec{B} = 0$ everywhere along the path but only that no net current is passing through the path.
- Sign of current : The current due to which B is produced in the same sense as dℓ (i.e. B · dℓ positive will be taken positive and the current which produces B in the sense opposite to dℓ will be negative.
- **Example 15.** Find the values of $\oint \vec{B} \cdot \vec{d\ell}$ for the loops L₁, L₂, L₃ in the figure shown. The sense of $\vec{d\ell}$ is mentioned in the figure.



Solution : for $L_1 = \oint \vec{B} \cdot \vec{d\ell} \mu_0(I_1 - I_2)$

here I₁ is taken positive because magnetic lines of force produced by I₁ is anti clockwise as seen from top. I₂ produces lines of \vec{B} in clockwise sense as seen from top. The sense of $\vec{d\ell}$ is anticlockwise as seen from top.

for L₂ :
$$\oint \vec{B} \cdot \vec{d\ell} = \mu_0$$
 (I₁ - I₂ + I₄) for L₃ : $\oint \vec{B} \cdot \vec{d\ell} = 0$

Uses : 2.4.1 To find out magnetic field due to infinite current carrying wire



By B.S.L. \vec{B} will have circular lines. $\vec{d\ell}$ is also taken tangent to the circle. $\oint \vec{B} \cdot \vec{d\ell} = \oint B \cdot d\ell$ $\because \theta = 0^{\circ} \text{ so } B \cdot d \oint d\ell = B 2\pi R$ ($\because B = \text{const.}$) Now by amperes law : $B 2\pi R = \mu_0 I$ \therefore $B = \frac{\mu_0 i}{2\pi R}$

2.4.2. Hollow current carrying infinitely long cylinder :

(I is uniformly distributed on the whole circumference)





2.4.3 Solid infinite current carrying cylinder : Assume current is uniformly distributed on the whole cross section area



Case (I) : r ≤ R

take an amperian loop inside the cylinder. By symmetry it should be a circle whose centre is on the axis of cylinder and its axis also coincides with the cylinder axis on the loop.

$$\begin{split} \oint \vec{B} \cdot \vec{d\ell} &= \oint B \cdot d\ell = B \oint d\ell = B. \ 2\pi r = \mu_0 \frac{1}{\pi R^2} \pi r^2 \\ B &= \frac{\mu_0 I r}{2\pi R^2} = \frac{\mu_0 J r}{2} \implies \vec{B} = \frac{\mu_0 \vec{J} \times \vec{r}}{2} \\ \textbf{Case (II) : } r \geq R \quad \oint \vec{B}. d\vec{\ell} = \oint B d\ell = B \oint d\ell = B . \ (2\pi r) = \mu_0 . I \\ \implies \qquad B = \frac{\mu_0 I}{2\pi r} \text{ also } \vec{B} \quad \frac{\mu_0 I}{2\pi r} (\hat{J} \times \hat{r}) = \frac{\mu_0 J \pi R^2}{2\pi r} \end{split}$$



Example 16. Consider a coaxial cable which consists of an inner wire of radius a surrounded by an outer shell of inner and outer radii b and c respectively. The inner wire carries an electric current i_0 and the outer shell carries an equal current in same direction. Find the magnetic field at a distance x from the axis where (a) x < a, (b) a < x < b (c) b < x < c and (d) x > c. Assume that the current density is uniform in the inner wire and also uniform in the outer shell.

Solution :



A cross-section of the cable is shown in figure. Draw a circle of radius x with the centre at the axis of the cable. The parts a, b, c and d of the figure correspond to the four parts of the problem. By symmetry, the magnetic field at each point of a circle will have the same magnitude and will be tangential to it. The circulation of B along this circle is, therefore,

 $\oint \vec{B}.d\vec{\ell} = B2\pi x$

in each of the four parts of the figure.

(a) The current enclosed within the circle in part b is io so that

$$\frac{i_0}{\pi a^2}$$
 . $\pi x^2 = \frac{i_0}{a^2} x^2$.

Ampere's law

$$\oint \vec{B}.\vec{d\ell} = \mu_0 i \text{ gives} \quad B.2\pi x = \frac{\mu_0 i_0 x^2}{a^2} \text{ or, } B = \frac{\mu_0 i_0 x}{2\pi a^2}$$

The direction will be along the tangent to the circle.

(b) The current enclosed within the circle in part b is i_0 so that

B $2\pi x = \mu_0 i_0$ or, B = $\frac{\mu_0 i_0}{2\pi x}$.

(c) The area of cross-section of the outer shell is $\pi c^2 - \pi b^2$. The area of cross-section of the outer shell within the circle in part c of the figure is $\pi x^2 - \pi b^2$.

Thus, the current through this part is $\frac{i_0(x^2-b^2)}{(c^2-b^2)}$. This is in the same direction to the current

io in the inner wire. Thus, the net current enclosed by the circle is

$$i_{\text{net}} = i_0 + \frac{i_0(x^2 - b^2)}{c^2 - b^2} = \frac{i_0(c^2 + x^2 - 2b^2)}{c^2 - b^2}.$$

From Ampere's law, B $2\pi x = \frac{i_0(c^2 + x^2 - 2b^2)}{c^2 - b^2}$ or, B = $\frac{\mu_0 i_0(c^2 + x^2 - 2b^2)}{2\pi x(c^2 - b^2)}$

(d) The net current enclosed by the circle in part d of the figure is $2i_0$ and hence

B
$$2\pi x = \mu_0 2i_0$$
 or, B = $\frac{\mu_0 I_0}{\pi x}$

Example 17. Figure shows a cross-section of a large metal sheet carrying an electric current along its surface. The current in a strip of width dl is λ dl where λ is a constant. Find the magnetic field at a point P at a distance y from the metal sheet.



Solution : Consider two strips A and C of the sheet situated symmetrically on the two sides of P (figure). The magnetic field at P due to the strip A is B₀ perpendicular to AP and that due to the strip C is B_c perpendicular to CP. The resultant of these two is parallel to the width AC of the sheet. The field due to the whole sheet will also be in this direction. Suppose this field has magnitude B.



The field on the opposite side of the sheet at the same distance will also be B but in opposite direction. Applying Ampere's law to the rectangle shown in figure.

$$2B\ell = \mu_0 \lambda \ell$$
 or $B = \frac{1}{2} \mu_0 \lambda$.

Note that it is independent of y.

Example 18.

Three identical long solenoids P, Q and R are connected to each other as shown in figure. If the magnetic field at the centre of P is 4 T, what would be the field at the centre of Q? Assume that the field due to any solenoid is confined within the volume of that solenoid only.



- IIT-JEE
- **Solution :** As the solenoids are identical, the currents in Q and R will be the same and will be half the current in P. The magnetic field within a solenoid is given by $B = \mu_0 ni$. Hence the field in Q will be equal to the field in R and will be half the field in P i.e., will be 2T.

3. MAGNETIC FORCE ON MOVING CHARGE

When a charge q moves with velocity \vec{v} , in a magnetic field \vec{B} , then the magnetic force experienced by moving charge is given by following formula :

- $\vec{F} = q(\vec{v} \times \vec{B})$ Put q with sign.
- \vec{v} : Instantaneous velocity
- \vec{B} : Magnetic field at that point.

Note :

- $\vec{F} \perp \vec{v}$ and also $\vec{F} \perp \vec{B}$
- $:: \vec{F} \perp \vec{v}$... power due to magnetic force on a charged particle is zero. (Use the formula of power
 - $P = \vec{F} \cdot \vec{v}$ for its proof).
- Since work done by magnetic force is zero in every part of the motion. The magnetic force cannot increase or decrease the speed (or kinetic energy) of a charged particle. Its can only change the direction of velocity.
- On a stationary charged particle, magnetic force is zero.
- If V || B, then also magnetic force on charged particle is zero. It moves along a straight line if only magnetic field is acting.
- **Example 19.** A charged particle of mass 5 mg and charge $q = +2\mu C$ has velocity $\vec{v} = 2\hat{i} 3\hat{j} + 4\hat{k}$. Find out the magnetic force on the charged particle and its acceleration at this instant due to magnetic field $\vec{B} = 3\hat{j} 2\hat{k}$. \vec{v} and \vec{B} are in m/s and Wb/m² respectively.

Solution :

 $\vec{F} = q\vec{v} \times \vec{B} = 2 \times 10^{-6} (2\hat{i} - 3\hat{j} \times 4\hat{k}) \times (3\hat{j} - 2\hat{k})$

 $= 2 \times 10^{-6} [-6\hat{i} + 4\hat{j} + 6\hat{k}] N$

By Newton's Law
$$\vec{a} = \frac{\vec{F}}{m} = \frac{2 \times 10^{-6}}{5 \times 10^{-6}} (-6\hat{i} + 4\hat{j} + 6\hat{k})$$

= 0.8 ($-3\hat{i} + 2\hat{j} + 3\hat{k}$) m/s²

3.1 Motion of charged particles under the effect of magnetic force

- Particle released if v = 0 then f_m = 0
 ∴ particle will remain at rest
- $\vec{V} \parallel \vec{B}$ here $\theta = 0$ or $\theta = 180^{\circ}$
 - \therefore F_m = 0 \therefore $\vec{a} = 0$ \therefore \vec{V} = const.
 - : particle will move in a straight line with constant velocity

Initial velocity $\vec{u} \perp \vec{B}$ and \vec{B} = uniform •

In this case \therefore B is in z direction so the magnetic force in z-direction will be zero $(\because \overrightarrow{F_m} \perp \vec{B})$.

Now there is no initial velocity in z-direction.

- particle will always move in xy plane. *.*..
- velocity vector is always $\perp \vec{B}$ \therefore $F_m = quB = constant$...

now
$$quB = \frac{mu^2}{R} \Rightarrow R = \frac{mu}{qB} = constant.$$

The particle moves in a curved path whose radius of curvature is same every where, such curve in a plane is only a circle.

... path of the particle is circular.

$$R = \frac{mu}{qB} = \frac{p}{qB} = \frac{\sqrt{2mk}}{qB}$$

here $p = \text{linear momentum}; k = \text{kinetic energy}$
now $v = \omega R \Rightarrow \omega = \frac{qB}{m} = \frac{2\pi}{T} = 2\pi f$
Time period $T = 2\pi m/qB$
frequency $f = qB/2\pi m$

Note :

• ω, f, T are independent of velocity.

 $T = 2\pi m/aB$

Example 20. A proton (p), *a*-particle and deuteron (D) are moving in circular paths with same kinetic energies in the same magnetic field. Find the ratio of their radii and time periods. (Neglect interaction between particles). $R = \frac{\sqrt{2mK}}{2mK}$

Solution :

$$\begin{array}{c} qB \\ \therefore \quad \mathsf{R}_{\mathsf{p}}:\mathsf{R}_{\alpha}:\mathsf{R}_{\mathsf{D}}=\frac{\sqrt{2\mathsf{m}\mathsf{K}}}{q\mathsf{B}}:\frac{\sqrt{2.4\mathsf{m}\mathsf{K}}}{2\mathsf{q}\mathsf{B}}:\frac{\sqrt{2.2\mathsf{m}\mathsf{K}}}{q\mathsf{B}}=1:1:\sqrt{2} \end{array}$$

:.
$$T_p: T_\alpha: T_D = \frac{2\pi m}{qB}: \frac{2\pi 4m}{2qB}: \frac{2\pi 2m}{qB} = 1:2:2$$
 Ans

Example 21. A positive charge particle of charge q, mass m enters into a uniform magnetic field with velocity v as shown in the figure. There is no magnetic field to the left of PQ. Find



(ii) distance travelled in the magnetic field

(i) time spent, (iii) impulse of magnetic force.

Solution : The particle will move in the field as shown

IIT-JEE



Angle subtended by the arc at the centre = 2θ

- (i) Time spent by the charge in magnetic field $\omega t = 2\theta \Rightarrow \frac{qB}{m} t = 2\theta \Rightarrow t = \frac{2m\theta}{qB}$
- (ii) Distance travelled by the charge in magnetic field = $r(2\theta) = \frac{mv}{qB}$. 2 θ
- (iii) Impulse = change in momentum of the charge = $(-mv \sin \theta \,\hat{i} + mv \cos \theta \,\hat{j}) (mv \sin \theta \,\hat{i} + mv \cos \theta \,\hat{j})$ = $-2mv \sin \theta \,\hat{i}$
- **Example 22.** In the figure shown the magnetic field on the left of 'PQ' is zero and on the right of 'PQ' it is uniform. Find the time spent in the magnetic field.



Example 23. A uniform magnetic field of strength 'B' exists in a region of width 'd'. A particle of charge 'q' and mass 'm' is shot perpendicularly (as shown in the figure) into the magnetic field. Find the time spend by the particle in the magnetic field if



Solution : (i) $d > \frac{mu}{qB}$ means d > R $\therefore t = \frac{T}{2} = \frac{\pi m}{qB}$ (ii) $\sin \theta = \frac{d}{R}$



Example 24. What should be the speed of charged particle so that it can't collide with the upper wall? Also find the coordinate of the point where the particle strikes the lower plate in the limiting case of velocity.

→u



≻X

Solution : (i) The path of the particle will be circular larger the velocity, larger will be the radius. For particle not to s



strike R < d

$$\Rightarrow v < \frac{qBd}{m}$$

(ii) for limiting case v =
$$\frac{qBd}{m}$$
; R = d

 \therefore coordinate = (-2d, 0, 0)

3.2 Helical path :

If the velocity of the charge is not perpendicular to the magnetic field, we can break the velocity in two components $-v_{\parallel}$, parallel to the field and v_{\perp} , perpendicular to the field. The components v_{\parallel} remains unchanged as the force $q\vec{v}\times\vec{B}$ is perpendicular to it. In the plane perpendicular to the field, the particle

traces a circle of radius r = $\frac{mv_{\perp}}{qB}$ as given by equation. The resultant path is helix.

Complete analysis :

Let a particle have initial velocity in the plane of the paper and a constant and uniform magnetic field also in the plane of the paper.



The particle starts from point A₁.

It completes its one revolution at A_2 and 2^{nd} revolution at A_3 and so on. X-axis is the tangent to the helix points

A₁, A₂, A₃,all are on the x-axis. distance $A_1A_2 = A_3A_4 = \dots = v \cos\theta$. T = pitch T = Time period where Let the initial position of the particle be (0, 0, 0) and v sin θ in +y direction. Then in x : $F_x = 0$, $a_x = 0$, $v_x = constant = v cos\theta$, $x = (v cos\theta)t$ In y-z plane : From figure it is clear that $y = R \sin\beta$, $v_y = v \sin\theta \cos\beta$ $z = -(R - R \cos \beta)$ vsinθ $v_z = v \sin\theta \sin\beta$ vsin0 acceleration towards centre = $(v\sin\theta)^2/R = \omega^2 R$ βor⊭t $a_y = -\omega^2 R \sin\beta$, $a_z = -\omega^2 R \cos\beta$ ÷. At any time : the position vector of the particle (or its displacement w.r.t. initial position) $\vec{r} = x\hat{i} + y\hat{j} + z\hat{k}$, x,y,z already found velocity $\vec{v} = v_x \hat{i} + v_y \hat{j} + v_z \hat{k}$, v_x, v_y, v_z already found $\vec{a} = a_x \hat{i} + a_y \hat{j} + a_z \hat{k}$, a_x , a_y , a_z already found

 $\text{Radius } q(v \sin \theta) B = \frac{m(v \sin \theta)^2}{R} \quad \Rightarrow \quad R = \frac{mv \sin \theta}{qB} \Rightarrow \omega = \frac{v \sin \theta}{R} = \frac{qB}{m} = \frac{2\pi}{T} = 2\pi f.$

3.3 Charged Particle in **E**&**B**

When a charged particle moves with velocity \vec{V} in an electric field \vec{E} and magnetic field \vec{B} , then. Net force experienced by it is given by following equation.

 $\vec{F} = q\vec{E} + q(\vec{V}x\vec{B})$

Combined force is known as Lorentz force.

Ē∥B∥v



In above situation particle passes undeviated but its velocity will change due to electric field. Magnetic force on it = 0.

Case(i): $\vec{E} \parallel \vec{B}$ and uniform $\theta \neq 0$, 180° (\vec{E} and \vec{B} are constant and uniform)



$$\vec{r} = \{(V_0 \cos \theta)t + \frac{1}{2} \frac{qE}{m}t^2\} \hat{i} + R \sin \omega t \hat{j} + (R - R \cos \omega t)(-\hat{k}) \\ \vec{V} = \left(V_0 \cos \theta + \frac{qE}{m}t\right)\hat{i} + (V_0 \sin \theta) \cos \omega t \hat{j} + V_0 \sin \theta \sin \omega t (-\hat{k}) \\ \vec{a} = \frac{qE}{m}\hat{i} + \omega^2 R[-\sin \beta \hat{j} - \cos \beta \hat{k}]$$

$$\begin{array}{c} \gamma & \nabla_{0} \text{Sine} \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & &$$

- **Example 25.** A long, straight wire carries a current i. A particle having a positive charge q and mass m kept at a distance x_0 from the wire is projected towards it with a speed v as shown in figure. Find the minimum separation between the wire and the particle
- **Solution :** Let the particle be initially at P (figure). Take the wire as the Y-axis and the foot of perpendicular from P to the wire as the origin. Take the line OP as the X-axis. We have, $OP = x_0$. The magnetic field B at any point to the right of the wire is along the positive Z-axis. The magnetic force on the particle is, therefore, in the X-Y plane. As there is no initial velocity along the Z-axis, the motion will be in the X-Y plane. Also, its speed remains unchanged. As the magnetic field is not uniform, the particle does not go along a circle. The force at time t is $\vec{F} = a\vec{v} \times \vec{B}$

$$= q(v_x \vec{i} + v_y \vec{j}) \times \left(\frac{\mu_0 i}{2\pi x} \hat{k}\right)$$

$$= -\vec{j}qv_x \frac{\mu_0 i}{2\pi x} + \vec{i} qv_y \frac{\mu_0 i}{2\pi x}.$$
Thus $a_x = \frac{F_x}{m} = \frac{\mu_0 q i}{2\pi m} = \lambda \frac{v_y}{x}$ (i)
where $\lambda = \frac{\mu_0 q i}{2\pi m}.$
Also, $a_x = \frac{dv_x}{dt} = \frac{dv_x}{dx} \frac{dx}{dt} = \frac{v_x dv_x}{dx}$ (ii)
Also, $a_x = \frac{dv_x}{dt} = \frac{dv_x}{dx} \frac{dx}{dt} = \frac{v_x dv_x}{dx}$ (iii)
From (i), (ii) and (iii), $\frac{v_y dv_y}{dx} = \frac{-\lambda v_y}{x}$ or, $\frac{dx}{x} = \frac{-dv_y}{\lambda}$
Initially $x = x_0$ and $v_y = 0$. At minimum separation from the wire, $v_x = 0$ so that $v_y = v$.

Thus
$$\int_{x_0}^{x} \frac{dx}{x} = \int_{0}^{v} \frac{dv_y}{-\lambda}$$
 or, $\ln \frac{x}{x_0} = -\frac{v}{\lambda}$ or, $x = x_0 e^{v/\lambda} = x_0 e^{-\frac{z/n}{\mu_0 c}}$

Example 26. An electron is released from the origin at a place where a uniform electric field E and a uniform magnetic field B exist along the negative Y-axis and the negative Z-axis respectively. Find the displacement of the electron along the Y-axis when its velocity becomes perpendicular to the electric field for the first time.

Solution : Let us take axes as shown in figure. According to the right-handed system, the Z-axis is upward in the figure and hence the magnetic field is shown downwards. At any time, the velocity of the electron may be written as

 $\vec{u} = u_{v}\vec{i} + u_{v}\vec{j}$

The electric and magnetic fields may be written as

 $\vec{E} = -\vec{E_i}$ and $\vec{B} = -\vec{B_k}$

respectively. The force on the electron is $\vec{F} = -e(\vec{E} + \vec{u} \times \vec{B}) = e\vec{E}\vec{j} + e\vec{B}(u_v\vec{i} - u_v\vec{j})$

Thus, $F_x = eu_y B$ and $F_y = e(E - u_x B)$.

The components of the acceleration are

$$a_{x} = \frac{du_{x}}{dt} = \frac{eB}{m}u_{y} \qquad \dots (i)$$

and $a_{y} = \frac{du_{y}}{dt} = \frac{e}{m}(E - u_{x}B)$. $\dots (ii)$
We have,
$$\frac{d^{2}u_{y}}{dt} = -\frac{eB}{m}\frac{du_{x}}{dt} = -\frac{eB}{m}\cdot\frac{eB}{m}u_{y} = -\omega^{2}u_{y}$$

V

$$\frac{d^2 u_y}{dt^2} = -\frac{eB}{m} \frac{du_x}{dt} = -\frac{eB}{m} \cdot \frac{eB}{m} u_y = -\omega^2 u_y$$

where $\omega = \frac{eB}{m}$ (iii)

This equation is similar to that for a simple harmonic motion. Thus, $u_y = A \sin(\omega t + \delta)$(iv)

and hence, $\frac{du_y}{dt} = A \omega \cos (\omega t + \delta)$

At t = 0,
$$u_y = 0$$
 and $\frac{du_y}{dt} = \frac{F_y}{dt} = \frac{eE}{m}$.

Putting in (iv) and (v),

$$\delta = 0 \text{ and } A = \frac{eE}{m\omega} \frac{E}{B}$$
.
Thus, $u_y = \frac{E}{B} \sin \omega t$.

The path of the electron will be perpendicular to the Y-axis when $u_v = 0$. This will be the case for the first time at t where

.....(v)

or $t = \frac{\pi}{\omega} = \frac{\pi m}{eB}$ $\sin \omega t = 0$ or $\omega t = \pi$ Also, $u_y = \frac{dy}{dt} = \frac{E}{B} \sin \omega t$ or $\int_{0}^{y} dy = \frac{E}{B} \sin \omega t \, dt$ or, $y = \frac{E}{B\omega} (1 - \cos \omega t).$ At $t = \frac{\pi}{\omega}$, $y = \frac{E}{B\omega}(1 - \cos \pi) = \frac{2E}{B\omega}$



IIT-JEE

Thus, the displacement along the Y-axis is $\frac{2E}{B\omega} = \frac{2Em}{BeB} = \frac{2Em}{eB^2}$. Ans.

3.4 Magnetic force on A current carrying wire :

Suppose a conducting wire, carrying a current i, is placed in a magnetic field \vec{B} . Consider a small element $d\ell$ of the wire (figure). The free electrons drift with a speed v_d opposite to the direction of the current. The relation between the current i and the drift speed v_d is



 $i = jA = nev_dA$.

Here A is the area of cross-section of the wire and n is the number of free electrons per unit volume. Each electron experiences an average (why average?) magnetic force

....(i)

 $\vec{f} = -\vec{ev}_d \times \vec{B}$

The number of free electrons in the small element considered in nAd ℓ . Thus, the magnetic force on the wire of length d ℓ is

 $d\vec{F} = (nAd\ell)(-e\vec{v}_d \times \vec{B})$

If we denote the length d ℓ along the direction of the current by $d\vec{\ell}$, the above equation becomes

 $d\vec{F} = nAev_{d}\vec{d\ell} \times \vec{B}$.

Using (i), $d\vec{F} = id\vec{\ell} \times \vec{B}$.

The quantity $id\vec{\ell}$ is called a current element.

 $\overrightarrow{F_{res}} = \int \overrightarrow{dF} = \int i d\vec{\ell} \times \vec{B} = i \quad \int \vec{d\ell} \times \vec{B} \qquad (\because i \text{ is same at all points of the wire.})$

If \vec{B} is uniform then $\vec{F}_{res} = i(\int \vec{d\ell}) \times \vec{B}$

$$\vec{F}_{res} = i \vec{L} \times \vec{B}$$

Here $\vec{L} = \int d\vec{\ell}$ = vector length of the wire = vector connecting the end points of the wire.

$$\Rightarrow \overbrace{P \downarrow}^{I} Q$$

Note :

• If a current loop of any shape is placed in a uniform \vec{B} then \vec{F}_{res} on it = 0 ($\because \vec{L} = 0$).

3.5 Point of application of magnetic force :

On a straight current carrying wire the magnetic force in a uniform magnetic field can be assumed to be acting at its mid point.



This can be used for calculation of torque.

Suppose the field and the current have directions as

Example 27. A wire is bent in the form of an equilateral triangle PQR of side 20 cm and carries a current of 2.5 A. It is placed in a magnetic field B of magnitude 2.0 T directed perpendicularly to the plane of the loop. Find the forces on the three sides of the triangle.

Solution :

shown in figure. The force on PQ is $\vec{E} = i\vec{\ell} \times \vec{B}$

or $F_1 = 2.5 \text{ A} \times 20 \text{ cm} \times 2.0 \text{ T} = 1.0 \text{ N}$

The rule of vector product shows that the force F_1 is perpendicular to PQ and is directed towards the inside of the triangle.



The forces \vec{F}_2 and \vec{F}_3 on QR and RP can also be obtained similarly. Both the forces are 1.0 N directed perpendicularly to the respective sides and towards the inside of the triangle.

The three forces \vec{F}_1 , \vec{F}_2 and \vec{F}_3 will have zero resultant, so that there is no net magnetic force on the triangle. This result can be generalised. Any closed current loop, placed in a homogeneous magnetic field, does not experience a net magnetic force.

Example 28. Figure shows two long metal rails placed horizontally and parallel to each other at a separation y. A uniform magnetic field B exists in the vertically upward direction. A wire of mass m can slide on the rails. The rails are connected to a constant current source which drives a current i in the circuit. The friction coefficient between the rails and the wire is μ .



- (a) What soluble the minimum value of μ which can prevent the wire from sliding on the rails?
- (b) Describe the motion of the wire if the value of μ is half the value found in the previous part.
- Solution: (a) The force on the wire due to the magnetic field is

 $\vec{F} = i\vec{\ell} \times \vec{B}$ or F = iyB

It acts towards right tin the given figure. If the wire does not slide on the rails, the force of friction by the rails should be equal to F. If μ_0 be the minimum coefficient of friction which can prevent sliding, this force is also equal to μ_0 mg. Thus,

$$\mu_0 \text{ mg} = \text{iyB} \quad \text{or} \quad \mu_0 = \frac{\text{iyB}}{\text{mg}}$$

(b) If the friction coefficient is $\mu = \frac{\mu_0}{2} = \frac{iyB}{2 mg}$, the wire will slide towards right. The frictional

force by the rails is $f = \mu mg = \frac{iyB}{2}$ towards left.

The resultant force is $iyB - \frac{iyB}{2} = \frac{iyB}{2}$ towards right. The acceleration will be $a = \frac{iyB}{2m}$. The wire will slide towards right with this acceleration.

Example 29. In the figure shown a semicircular wire is placed in a uniform B directed toward right. Find the resultant magnetic force and torque on it.



Solution :

The wire is equivalent to

 $\theta = 0$

÷

≻B Ī 2R $F_{res} = 0$

Ans.



÷.

$$\tau = \int_{0}^{\pi/2} i(Rd\theta) B \sin(90 - \theta) . 2R \cos \theta$$

$$\tau = \frac{i\pi R^{2}}{2} B \qquad \Rightarrow \qquad \vec{\tau} = \frac{i\pi R^{2}}{2} B(-\hat{j}) \text{ Ans.}$$

Solution :

 $F_{res} = 0$, (:: loop)



and $\vec{\tau} = i\pi R^2 B(-\hat{j})$ using the above method

In the figure shown find the resultant magnetic force and torque about 'C', and 'P'. Example 31



 $\vec{F}_{nett} = I . 2R . B$ Solution :

: wire is equivalent to



Force on each element is radially outward : $\tau_c=0$ point about



 $P = \int_{0}^{\pi} [I(Rd\theta)B\sin 90^{\circ}] R\sin\theta = 2IBR^{2}$

Ans.

Example 32. Prove that magnetic force per unit length on each of the infinitely long wire due to each other is $\mu_0 I_1 I_2 / 2\pi d$. Here it is attractive also.





IIT-JEE



Note :

Definition of ampere (fundamental unit of current) using the above formula. If I₁ = I₂ = 1A, d = 1m then F = 2 × 10⁻⁷ N

:. "When two very long wires carrying equal currents and separated by 1m distance exert on each other a magnetic force of 2×10^{-7} N on 1m length then the current is 1 ampere."

• The above formula can also be applied if to one wire is infinitely long and the other is of finite length. In this case the force per unit length on each wire will not be same.

$$I_1 \bigoplus_{d=Q}^{P} I_2 \bigoplus_{\ell}^{\ell}$$

Force per unit length on PQ = $\frac{\mu_0 I_1 I_2}{2\pi d}$

(attractive)

 If the currents are in the opposite direction then the magnetic force on the wires will be repulsive.

Example 33. Find the magnetic force on the loop 'PQRS' due to the loop wire.

Solution :
$$F_{res} = \frac{\mu_0 I_1 I_2}{2\pi a} a(-\hat{i}) + \frac{\mu_0 I_1 I_2}{2\pi (2a)} a(\hat{i}) = \frac{\mu_0 I_1 I_2}{4\pi} (-\hat{i})$$

IIT-JEE



TORQUE ON A CURRENT LOOP: 4.

When a current-carrying coil is placed in a uniform magnetic field the net force on it is always zero. However, as its different parts experience forces in different directions so the loop may experience a torque (or couple) depending on the orientation of the loop and the axis of rotation. For this, consider a rectangular coil in a uniform field B which is free to rotate about a vertical axis PQ and normal to the plane of the coil making an angle θ with the field direction as shown in figure (A).



Axis of rotation (A)

The arms AB and CD will experience forces B(NI)b vertically up and down respectively. These two forces together will give zero net force and zero torque (as are collinear with axis of rotation), so will have no effect on the motion of the coil.

Now the forces on the arms AC and BD will be BINL in the direction out of the page and into the page respectively, resulting in zero net force, but an anticlockwise couple of value

 $\tau = F \times Arm = BINL \times (b \sin\theta)$

i.e. $\tau = BIA \sin \theta$ with A = NLb

.....(i)

Now treating the current–carrying coil as a dipole of moment $\vec{M} = I\vec{A}$ Eqn. (i) can be written in vector form as

$$\vec{\tau} = \vec{M} \times \vec{B}$$
 with $\vec{M} = I\vec{A} = NIA\vec{n}$

.....(ii) This is the required result and from this it is clear that :

- (1) Torque will be minimum (= 0) when $\sin\theta = \min = 0$, i.e., $\theta = 0^{\circ}$, i.e. 180° i.e., the plane of the coil is perpendicular to magnetic field i.e. normal to the coil is collinear with the field [fig. (A) and (C)]
- (2) Torque will be maximum (= BINA) when $\sin\theta = \max = 1$, i.e., $\theta = 90^{\circ}$ i.e. the plane of the coil is parallel to the field i.e. normal to the coil is perpendicular to the field. [fig.(B)].
- (3) By analogy with dielectric or magnetic dipole in a field, in case of current-carrying in a field.

$$U = -\vec{M} \cdot \vec{B}$$
 with $F = -\frac{dU}{dr}$

and W = MB(1 - $\cos\theta$)

The values of U and W for different orientations of the coil in the field are shown in fig.

B ₿ $\theta = 180^{\circ}$ (M is antiparallel to B) $\theta = 90^{\circ} (M \text{ is } \perp \text{ to } B)$ $\theta = 0^{\circ}$ (M is parallel to B) $\tau = 0 = \min$ $\tau = MB = max$ $\tau = 0$ W = 0 = minW = MBW = 2MB = maxU = -MB = minU = MB = maxU = 0Stable equilibrium No equilibrium Unstable equilibrium (A) (B) (C)

- (4) Instruments such as electric motor, moving coil galvanometer and tangent galvanometers etc. are based on the fact that a current–carrying coil in a uniform magnetic field experiences a torque (or couple).
- **Example 34.** A loop with current I is in the field of a long straight wire with current I₀. The plane of the loop is perpendicular to the straight wire. Find torque acting on the loop.



 $(-MB \cos 90^\circ) - (-MB\cos 90^\circ) = KE$

Example 36.	In the shown figure a conducting ring of mass $m = 2kg$ and radius $R = 0.5 m$. lies on a smooth horizontal plane with its plane B
	vertical. The ring carries a current of I = $\frac{1}{\pi}$ A. A horizontal uniform
Answer :	magnetic field of B = 12T is switched on at t = 0. The initial angular acceleration α in rad./sec ² of the ring will be 4x if x is : 3
Solution :	$\tau_{y\text{-axis}} = I_{y\text{-axis}} \alpha$ $(I.\pi r^2) B = 1/2 \text{ mr}^2 \alpha$ $\alpha = 12 \text{ rad/sec}^2 \qquad \therefore \qquad X = 3$
Example 37.	A current carrying ring, carrying a constant current $\frac{2}{\pi}$ Amp., radius 1m,
	mass $\frac{2}{3}$ kg and having 10 windings is free to rotate about its tangential $\left(\begin{array}{c} \\ \\ \end{array} \right)$
Answer :	vertical axis. A uniform magnetic field of 1 tesla is applied perpendicular to its plane. How much minimum angular velocity (in rad/sec.) should be given to the ring in the direction shown, so that it can rotate 270° in that direction. Write your answer in nearest single digit in rad/sec. 9
Solution :	to reach $\theta = 270^{\circ}$, it has to cross the potential energy barrier at $\theta = 180^{\circ}$ and to cross $\theta = 180^{\circ}$ angular velocity at $\theta = 180^{\circ}$ should be 0 ⁺ k _i + U _i = k _f + U _y $\frac{1}{2} \left(\frac{3}{2} MR^2\right) \omega^2$ + (-Mi AB cos 0°) = 0 + (-NiAB cos 180°)
	$\omega = \sqrt{80} \approx 9 \text{ rad/sec.}$

5. **TERRESTRIAL MAGNETISM (EARTH'S MAGNETISM) :**

5.1 Introduction :

The idea that earth is magnetised was first suggested towards the end of the sixteen'th century by Dr. William Gilbert. The origin of earth's magnetism is still a mater of conjecture among scientists but it is agreed upon that the earth behaves as a magnetic dipole inclined at a small angle (11.5°) to the earth's axis of rotation with its south pole pointing north. The lines of force of earth's magnetic field are shown in figure which are parallel to the earth's surface near the equator and perpendicular to it near the poles. While discussing magnetism of the earth one should keep in mind that:

- The magnetic meridian at a place is not a line but a (a) vertical plane passing through the axis of a freely suspended magnet, i.e., it is a plane which contains the place and the magnetic axis.
- (b) The geographical meridian at a place is a vertical plane which passes through the line joining the geographical north and south, i.e., it is a plane which contains the place and earth's axis of rotation, i.e., geographical axis.
- The **magnetic Equator** is a great circle (a circle with the centre at earth's centre) on earth's (c) surface which is perpendicular to the magnetic axis. The magnetic equator passing through Trivandrum in South India divides the earth into two hemispheres. The hemisphere containing south polarity of earth's magnetism is called the northern hemisphere (NHS) while the other, the southern hemisphere (SHS).
- (d) The magnetic field of earth is not constant and changes irregularly from place to place on the surface of the earth and even at a given place it varies with time too.

ato $\theta = 0$

Geoa

Axis

BH = BI

B[√]=0



5.2 Elements of the Earth's Magnetism :

The magnetism of earth is completely specified by the following three parameters called elements of earth's magnetism :

(a) Variation or Declination θ : At a given place the angle between the geographical meridian and the magnetic meridian is called declination, i.e., at a given place it is the angle between the geographical north-south direction and the direction indicated by a magnetic compass needle, Declination at a place is expressed at θ^{0} E or θ^{0} W depending upon whether the north pole of the compass needle lies to the east (right) or to the west (left) of the geographical north-south direction. The declination at London is 10°W means that at London the north pole of a compass needle points 10°W, i.e., left of the geographical north.



Here, it is worthy to note that as the northern hemisphere contains south polarity of earth's magnetism, in it the north pole of a freely suspended magnet (or pivoted compass needle) will dip downwards, i.e., towards the earth while the opposite will take place in the southern hemisphere.



Angle of dip at a place is measured by the instrument called Dip-Circle in which a magnetic needle is free to rotate in a vertical plane which can be set in any vertical direction. Angle of dip at Delhi is 42°.

(c) Horizontal Component of Earth's Magnetic Field B_H : At a given place it is defined as the component of earth's magnetic field along the horizontal in the magnetic meridian. It is represented by B_H and is measured with the help of a vibration or deflection magnetometer. At Delhi the horizontal component of the earth's magnetic field is 35 μT, i.e., 0.35 G.

If at a place magnetic field of earth is B₁ and angle of dip $\phi,$ then in accordance with figure (a).

$$B_{H} = B_{I} \cos \phi \quad \text{and} \quad B_{v} = B_{I} \sin \phi \qquad \dots \dots (1)$$

so that,
$$\tan \phi = \frac{B_{v}}{B_{u}} \quad \text{and} \quad B_{I} = \sqrt{B_{H}^{2} + B_{v}^{2}} \qquad \dots \dots (2)$$

Problem 1. Two short magnet A and B of magnetic dipole moments M₁ and M₂ respectively are placed as shown. The axis of 'A' and the equatorial line of 'B' are the same. Find the magnetic force on one magnet due to the other.





	(v) $B = B_1 - B_2 = \left(\frac{\mu_0 I}{2a} \times \frac{1}{2} - \frac{\mu_0 I}{2b} \times \frac{1}{2}\right) = \frac{\mu_0 I}{4} \left(\frac{1}{a} - \frac{1}{b}\right)$
	(vi) $B = B_1 - B_2 = \frac{\mu_0 I}{2R} - \frac{\mu_0 I}{2\pi R} = \frac{\mu_0 I}{2 R} \left(1 - \frac{1}{\pi}\right)$
	(vii) B = B ₁ + B ₂ = $\frac{\mu_0 I}{2R} + \frac{\mu_0 I}{2\pi R} = \frac{\mu_0 I}{2R} \left(1 + \frac{1}{\pi}\right)$
	(viii) $B = B_1 - B_2 = \frac{\mu_0 I}{2a} - \frac{\mu_0 I}{2b} \times \frac{\theta}{2\pi} = \frac{\mu_0 I \theta}{4\pi} \left(\frac{1}{a} - \frac{1}{b}\right)$
Problem 6.	A thin solenoid of length 0.4 m and having 500 turns of wire carries a current 1A; then find th magnetic field on the axis inside the solenoid.
Answer :	$5\pi \times 10^{-4} \text{ T.}$
Solution :	$B = \mu_0 n i = \frac{\mu_0 N i}{\ell} = 5\pi \times 10^{-4} T.$
Problem 7.	A charged particle of charge 2C thrown vertically upwards with velocity 10 m/s. Find the magnetic force on this charge due to earth's magnetic field. Given vertical component of the earth = 3μ T and angle of dip = 37° .
Colution :	A = 270 By $B = 4$ $A = 40$
Solution :	$\tan 37^{\circ} = \frac{1}{B_{H}} \implies B_{H} = \frac{1}{3} \times 3 \times 10^{-6} \text{ I}$ $F = q \vee B_{H} = 8 \times 10^{-5} \text{ N}$
Problem 8.	A charged particle has acceleration $\vec{a} = 2\hat{i} + x\hat{j}$ in a magnetic field $\vec{B} = -3\hat{i} + 2\hat{j} - 4\hat{k}$. Find the value of x.
Solution :	$\because \vec{F} \perp \vec{B} \therefore \vec{a} \perp \vec{B} \therefore \vec{a} \cdot \vec{B} = 0$
	\therefore $(2\hat{i} + x\hat{j}) \cdot (-3\hat{i} + 2\hat{j} - 4\hat{k}) = 0$
	$\Rightarrow -6 + 2x = 0 \Rightarrow x = 3.$
Problem 9.	Repeat above question if the charge is -ve and the angle made by the boundary with the velocity is $\frac{\pi}{6}$.
Solution :	(i) $2\pi - 2\theta = 2\pi - 2\frac{\pi}{6} = 2\pi - \frac{\pi}{3} = \frac{5\pi}{3} = \omega t = \frac{qBt}{m} \Rightarrow t = \frac{5\pi m}{3qB}$
	$\times \times \times \times \times$
	$\theta = \pi/6$ × × × ×
	V K X X X X
	(((((((((((((((((((
	$\begin{array}{c} \mathbf{x} \\ $
	(ii) Distance travelled s = r($2\pi - 2\theta$) = $\frac{5\pi r}{3}$
	(iii) Impulse = charge in linear momentum = m($-v \sin \theta \hat{i} + v \cos \theta \hat{j}$) – m($v \sin \theta \hat{i} + v \cos \theta \hat{j}$)
	$= -2mv \sin \theta \hat{i} = -2mv \sin \frac{\pi}{6} \hat{i} = -mv \hat{i}$
Problem 10.	A particle of charge q and mass m is projected in a uniform and constant magnetic field of strength B. The initial velocity vector \vec{v} makes angle ' θ ' with the \vec{B} . Find the distance travelled by the particle in time 't'.

IIT-JEE

Answer :

vt

- Solution : Speed of the particle does not change there fore distance covered by the particle is s = vt
- **Problem 11.** Two long wires, carrying currents i_1 and i_2 , are placed perpendicular to each other in such a way that they just avoid a contact. Find the magnetic force on a small length $d\ell$ of the second wire situated at a distance ℓ from the first wire.



Solution : The situation is shown in figure. The magnetic field at the site of $d\ell$, due to the first wire is,

$$\mathsf{B} = \frac{\mu_0 \mathsf{I}_1}{2\pi\ell}$$

This field is perpendicular to the plane of the figure going into it. The magnetic force on the length $d\ell$ is,

$$dF = i_2 d\ell B \sin 90^\circ = \frac{\mu_0 i_1 i_2 d\ell}{2\pi\ell}$$

This force is parallel to the current i1.

Problem 12. In the figure shown the wires AB and PQ carry constant currents I_1 and I_2 respectively. PQ is of uniformly distributed mass 'm' and length ' ℓ '. AB and PQ are both horizontal and kept in the same vertical plane. The PQ is in equilibrium at height 'h'. Find



- (i) 'h' in terms of I1, I2, ℓ , m, g and other standard constants.
- (ii) If the wire PQ is displaced vertically by small distance prove that it performs SHM. Find its time period in terms of h and g.

Solution :

(i)

$$\begin{array}{ll} \mbox{Magnetic repulsive force balances the weight.} \\ \mbox{$\frac{\mu_0 I_1 I_2}{2\pi h}$ ℓ mg \Rightarrow $h = \frac{\mu_0 I_1 I_2 \ell}{2\pi mg}$ \end{array}$$

 (ii) Let the wire be displaced downward by distance x(<< h). Magnetic force on it will increase, so it goes back towards its equilibrium position. Hence it performs oscillations.

$$F_{\text{res}} = \frac{\mu_0 I_1 I_2}{2\pi (h-x)} \ell - mg = \frac{mgh}{h-x} - mg = \frac{mg(h-h+x)}{h-x} = \frac{mg}{h-x} x \cong \frac{mg}{h} \text{ x for } x << h$$

$$\therefore \quad T = 2\pi \sqrt{\frac{m}{mg/h}} = 2\pi \sqrt{\frac{h}{g}} \quad \text{Ans.}$$